DATA SHEET

GIESSBETON RUNDE AUFLAGE - with plastic clip

Description

Spacer with round support made of cast concrete. With plastic clip for easy attachment to the reinforcement. Excellent for exposed concrete because of only one point of contact with the formwork.

Application

The spacer is attached to the reinforcement with the plastic clip. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

GIESSBETON RUNDE AUFLAGE - with plastic clip

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Pallet
GBRA20KK	20	4 - 14	512	20.480
GBRA25KK	25	4 - 14	448	17.920
GBRA30KK	30	4 - 14	320	12.800
GBRA35KK	35	4 - 14	320	12.800
GBRA40KK	40	4 - 14	256	10.240
GBRA45KK	45	4 - 14	256	10.240
GBRA50KK	50	4 - 14	192	7.680
GBRA60KK	60	4 - 14	147	5.880



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.