DATA SHEET

NAGELSTOPFEN - for exposed concrete

Description

Nail plug made of platic for exposed concrete for Gewindehülse-PLUS (Item-No. GWHP15/GH).

Application

The nail plug is nailed to the formwork and the Gewindehülse-PLUS is placed on it. The nail plug ensures a secure hold of the Gewindehülse-PLUS during concreting. Loosen and unscrew the nail plug, if it does not remain on the formwork during stripping, with an 8 mm Allen key / offset screwdriver in the integrated hexagon socket of the nail plug. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polypropylene (PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants


DATA SHEET

NAGELSTOPFEN - for exposed concrete

Item no.	Pcs/ Bag	Pcs/ Pallet
GWHP15/NSS	100	16.000



Note: Protect from direct sunlight during storage.



For further documents
scan or click here!

Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/nagelstopfen-for-exposed-concrete/

Created: 30.10.2023