TECHNICAL DATA SHEET

KMX 65 / 60 BL

Beton Donatısı İçin Çelik Teller



KEMERİX

Kemerix is a cost efficient and time - saving solution for:

- Flooring industry.
- Tunnel applications.
- Precast industry.
- Residental applications.

ADVANTAGES

- High impact resistance.
- Improved structural ductility.
- Increased durability by providing crack control.
- Remarkably increased flexural strength.
- Exceptional control over cracking.

APPLICATION AREAS

- Heavy duty industrial floors,
- Jointless floors,
- Concrete pavements,
- Subway stations,
- Airports,
- Seaports,
- Logistics areas,
- Oil stations,
- Parking areas.

GEOMETRY AND PERFORMANCE



MATERIAL PROPERTIES

Type	Cold Drawn - Loose
Number Of Fibres Per Kg	3.200 Fibres/Kg
Total Fibre Length Per 15 Kg	2,9 Km/m³
Tensile Strength	1200 N/mm²

PRODUCT CERTIFICATE


CE TSE K-Q TSE/ISO-EN 9000 C-E TSE-ISO-EN 14000 TSE TS ISO 45001

Kemerix is certified for structural use according to TS 10513 and EN 14889-1 system 1). Kemerix® plant is ISO 9001, ISO 14001 and OHSAS 18001 certificed.


PACKAGING AND STORAGE



Bagging : 15 kg.



Pallet Weight : 1.200 kg.





TECHNICAL SUPPORT

Kemerli; technical support gives advice to determine the most suitable product for your project and the amount of use.

- The instant application support site.
- Product application and mixing information support.
- Our team of experts with you every moment.

444 7 489 - technical@kemerix.com

KEMERLİ®

Kemerli Metal Sanayi ve Ticaret A.Ş.
Center: O.S.B. 20. Cad. No: 62 38070 Melikgazi - Kayseri / TÜRKİYE P. +90 (352) 322 13 84
Branch: Çerkeşli O.S.B. Mah. İmes 17. Cadde No: 3 Dilovası - Kocaeli / TÜRKİYE
444 7 489 - www.kemerix.com.tr

/kemerixofficial