DATA SHEET

STOPFEN

Description

Plastic plugs for closing tie rod sleeves after demoulding and removal of cones.

Application

After removing the formwork, the tie anchor and the cone, the plug is driven into the tie hole with a rubber mallet. To make driving in easier, a second, inverted plug can be used as a driving-in aid. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

STOPFEN

Item no.	For tube Ø mm	Pcs/ Bag	Pcs/ Pallet
ST20	20	1.000	48.000
ST22	22	1.000	48.000
ST26	26	500	50.000
ST32	32	500	24.000



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/stopfen/

Created: 30.10.2023