DATA SHEET

ABSTANDHALTER MIT GRUNDPLATTE

Description

Plastic spacer with large contact area for use on soft surfaces.

Application

The spacer is positioned on the formwork, then the reinforcement is inserted into the clamping device. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

ABSTANDHALTER MIT GRUNDPLATTE

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Pallet
ATM1520	15 / 20	8 - 16	500	16.000
ATM2530	25 / 30	8 - 16	400	12.800
ATM4050	40 / 50	8 - 16	200	12.000
ATM5060	50 / 60	8 - 16	200	13.600
ATM7080	70 / 80	8 - 16	200	7.200
ATM90100	90 / 100	8 - 16	100	6.400



For further documents
scan or click here!

Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/abstandhalter-mit-grundplatte/

Created: 30.10.2023