DATA SHEET

KUPPLUNG

Description

Plastic coupling for combination of tie rod sleeves and fibre-reinforced concrete tubes. Suitable for tubes with Ø 22 mm.

Application

The coupling is inserted on both sides into a tie rod sleeve or fibre-reinforced concrete tube with an internal diameter of 22 mm. The usability of the product in the respective installation situation must be checked by the user!

Material

- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

KUPPLUNG

Item no.	For tube Ø mm	Fitting length mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
DIKU22	22	1	250	2.500	35.000



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/kupplung/

Created: 30.10.2023