DATA SHEET

FASERBETON EINZELABSTANDHALTER MIT HOHLKEHLE- 2 hooks lengthwise

Description

Extra strong single spacer made of fibre-reinforced concrete with groove and two lengthwise hooks for a secure hold on the reinforcement.

Application

The spacer is attached to the vertical reinforcement with the hooks. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

FASERBETON EINZELABSTANDHALTER MIT HOHLKEHLE- 2 hooks lengthwise

Item no.	Concrete cover mm	Cutting width mm	Width groove mm	Depth groove mm	Pcs/ Bag	Pcs/ Pallet
FBE2H20/30/10	20	30	12	10	250	8.000
FBE2H25/30/10	25	30	12	10	200	8.000
FBE2H30/30/10	30	30	12	10	200	8.000
FBE2H35/30/10	35	30	12	10	200	8.000
FBE2H40/30/10	40	30	12	10	200	8.000
FBE2H45/30/10	45	30	12	10	150	6.000
FBE2H50/30/10	50	30	12	10	150	6.000



Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

For further documents
scan or click here!

Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.