DATA SHEET

FEDERSTAHLBINDER

Description

Elastic spring clips for quick and easy connection of reinforcing steel. Completely without tools. Supplied on cardboard strips.

Application

The Federstahlbinder is hooked onto the first iron and bent and fastened over the second iron. The usability of the product in the respective installation situation must be checked by the user!

Material

- Steel
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

FEDERSTAHLBINDER

Item no.	Type	Ø mm	For steel 1 Ø mm	For steel 2 Ø mm	Pcs/ Strip	Pcs/ Box	Pcs/ Pallet
FST12/14-16	12/14-16	2,00	10 - 12	12 - 14 - 16	20	4.000	72.000
FST6/8	6/8	1,45	4 - 6	6 - 8	45	14.400	259.200
FST8/10	8/10	1,60	6 - 8	8 - 10	35	11.200	201.600
FST8/12	8/12	1,60	6 - 8	10 - 12	30	9.600	172.800
FST8/14	8/14	1,60	6 - 8	12 - 14	25	8.000	144.000
FST8/16	8/16	1,70	6 - 8	14 - 16	30	6.000	108.000
FST8/20	8/20	1,90	6 - 8	18 - 20	20	4.000	72.000
FST8/8	8/8	1,50	6 - 8	6 - 8	50	10.000	180.000



Further dimensions on request.

Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/federstahlbinder/

Created: 30.10.2023