DATA SHEET

RINGABSTANDHALTER - for iron 12 - 20 mm

Description

Plastic wheel spacers for vertical reinforcement.

Application

The spacer is clamped to the vertical reinforcement. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

RINGABSTANDHALTER - for iron 12 - 20 mm

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
R60/12-20	60	12 - 20	250	-	6.500
R75/12-20	75	12 - 20	250	-	4.500



Tested according to DBV leaflet „Abstandhalter“ DBV - c - L1/F/A.

Note: Protect from direct sunlight during storage.



For further documents
scan or click here!

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/ringabstandhalter-for-iron-12-20-mm/

Created: 30.10.2023