

SCHALROHR NEVOTUBE® "RECHTECK"**Description**

FORMWORK TUBE NEVOTUBE® "RECHTECK"

Flexibility:

Every producible dimension available within 2 to 3 working days. Delivered to construction site in customised lengths. Lengths of up to 12.5 m have already been realised.

Quality:

Suitable for exposed concrete quality SB4. According to the DBV leaflet "Fair-faced concrete", the creation of a test area is required for SB4 or strongly recommended for SB3. Resistant to direct exposure to moisture. No horizontal joints of the inner liner up to a length of 4 m.

Economy:

One concreting date for many columns. This ensures optimum construction progress. Extremely light and easy to handle during transport and assembly. No crane required in most cases. Columns can be stripped in seconds using a knife. No risk of damage to the exposed concrete surface.

Environmentally friendly:

Cleaning and return transport of the formwork is not necessary. No formwork oil required. Problem-free disposal.

Application

When setting up, do not force the formwork tubes over reinforcement or spacers that may be bent too large. Position on the foundation side in the axis and fix with a wooden cross. With square and rectangular pipes as well as special shapes, pay attention to the alignment of the formwork pipes. On the ceiling side, adjust the formwork vertically with tension belts and on-site tension and pressure-resistant push-pull props and secure against uplift.

Please also note the technical application notes under "further documents", see QR code on page 2 of the data sheet.

The usability of the product in the respective installation situation must be checked by the user!

Material

- Expanded Polystyrene (EPS)
- Polyvinyl Chloride (PVC)
- Tetra Pak® Cardboard
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



SCHALROHR NEVOTUBE® "RECHTECK"

Item no.	Dimension mm	Ø Outside mm	Chamfer ~ mm	Concreting speed m/h	Concrete required ~ m³/m	Weight ~ kg/m
TM2024	200 x 240	300	18	6	0,05	3,70
TM2025	200 x 250	300	27	6	0,05	3,70
TM2030	200 x 300	350	17	6	0,06	4,30
TM2425	240 x 250	330	24	6	0,06	4,00
TM2430	240 x 300	360	31	6	0,07	5,00
TM2435	240 x 350	400	33	5	0,08	5,60
TM24365	240 x 365	400	51	5	0,09	5,70
TM2440	240 x 400	450	25	5	0,10	6,80
TM2445	240 x 450	500	18	5	0,11	8,70
TM2530	250 x 300	360	38	6	0,08	5,00
TM2535	250 x 350	400	40	5	0,09	5,80
TM2540	250 x 400	450	31	5	0,10	6,50
TM2545	250 x 450	500	23	5	0,11	7,60
TM2550	250 x 500	550	18	4	0,13	7,90
TM3035	300 x 350	450	16	5	0,11	6,80
TM3040	300 x 400	470	38	4	0,12	7,30
TM3045	300 x 450	500	54	4	0,14	8,10
TM3050	300 x 500	550	47	3	0,15	8,80
TM3055	300 x 550	600	39	3	0,17	10,00
TM3060	300 x 600	650	35	3	0,18	11,20
TM3540	350 x 400	500	38	4	0,14	8,50
TM3545	350 x 450	550	26	3	0,16	8,80
TM3550	350 x 500	600	16	3	0,18	9,30
TM3560	350 x 600	685	16	3	0,21	12,20
TM4045	400 x 450	550	60	3	0,18	9,30
TM4050	400 x 500	600	48	3	0,20	10,00
TM4055	400 x 550	650	37	3	0,22	11,20
TM4060	400 x 600	700	28	3	0,24	12,30
TM4550	450 x 500	650	28	3	0,23	10,80
TM4555	450 x 550	685	33	3	0,25	12,50
TM4560	450 x 600	700	60	3	0,27	12,80
TM5060	500 x 600	750	37	3	0,30	14,20



For further documents
scan or click here!



SCHALROHR NEVOTUBE® "RECHTECK"

Item no.	Dimension mm	Ø Outside mm	Chamfer ~ mm	Concreting speed m/h	Concrete required ~ m³/m	Weight ~ kg/m
TR17524	175 x 240	330	25	6	0,04	2,80
TR17530	175 x 300	376	25	6	0,05	3,50
TR17540	175 x 400	479	25	6	0,07	5,00
TR2035	200 x 350	430	30	6	0,07	4,90
TR2040	200 x 400	488	30	5	0,08	5,80
TR2045	200 x 450	533	30	5	0,09	7,20
TR2050	200 x 500	580	30	5	0,10	7,60
TR2450	240 x 500	598	30	4	0,12	6,90
TR2455	240 x 550	640	30	4	0,13	8,90
TR2460	240 x 600	690	30	4	0,14	9,80
TR2555	250 x 550	645	30	4	0,14	9,00
TR2560	250 x 600	701	30	3	0,15	9,90
TR3555	350 x 550	696	30	3	0,18	9,60

Attention: Chamfer not always exactly 45°.

For top fair-faced concrete quality! Further dimensions on request. When using self-compacting concrete, the concreting speeds have to be halved.

Nevoga Group

FREILASSING | DE ZNOJMO | CZ BIESIEKIERZ | PL 
 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/schalrohr-nevotube-rechteck/>

Created: 30.10.2023

Page 3 / 3