

# Renderoc Plug 4

## Very fast setting, leakage blocking material

### Uses

For immediate action of stopping water leakages and drying surface wetness over any cementitious or mineral based surfaces

### Advantages

- Ready to use
- Easy to apply, powder form
- Very fast setting

### Description

Renderoc Plug 4 is applied in powder form for immediate action to eliminate the water leakages

Renderoc Plug provides an initial set time of 3-5 seconds.

### Technical support

Fosroc offers a comprehensive technical support service to specifiers, end users and contractors. It is also able to offer on-site technical assistance, an AutoCAD facility and dedicated specification assistance in locations all over the world.

### Properties

|                    |             |
|--------------------|-------------|
| <b>Curing time</b> | 3-5 seconds |
|--------------------|-------------|

Results above has tested at 23±2 °C.

### Instructions for use

#### Preparation

Areas to be patched should be cut back to a depth of 15 mm and given a good mechanical key. Feather-edges must not be allowed. Surface should be brushed clean to remove loose material, dust and laitance. Grease, slime or mould growth should be removed by steam cleaning or high-pressure water jetting. Aproprietary degreasing agent should be used for removal of light oil or grease contamination.

Areas to be patched should be wet.

#### Application

Renderoc Plug 4 has been applied in powder form. Suitable amount of powder has to be applied over water leakage with hand-knead and pressure has to be applied until curing occurred.

Renderoc Plug 4 can be applşied by mixing with water but as the curing time is very fast, low portions has to be mixed and applied immediately.

Protective equipment and wearing glowes is necessary during application

### Packaging

|                    |               |
|--------------------|---------------|
| Renderoc Plug 4    | 5-20 kg pails |
| <b>Consumption</b> |               |
| Renderoc Plug      | 2,00 kg/lt    |

### Cleaning

Renderoc Plug 4 products should be removed from tools, equipment and mixers with clean water immediately

### Limitations

Renderoc Plug 4 can react with humidity so while application unused material has to be protected by closing the packs.

### Storage

#### Shelf life

Renderoc Plug 4 has a shelf life of 12 months if kept in a dry store in the original, unopened bags or packs.

### Precautions

#### Health and safety

Renderoc Plug 4 contain powders which, can be harmful to the skin. During use, avoid inhalation of dust and contact with skin and eyes.

Wear suitable protective clothing, gloves, eye protection and respiratory protective equipment. The use of barrier creams provide additional skin protection. In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water.

In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. If swallowed, seek medical attention immediately - do not induce vomiting.

#### Fire

Renderoc Plug 4 is non-flammable.

For further information, refer to the Product Material Safety Data Sheet.

# Renderoc Plug 4

---

## Additional Information

Fosroc manufactures a wide range of complementary Products which include :

- waterproofing membranes & water stops
- joint sealants & filler boards
- cementitious & epoxy grouts
- specialized flooring materials

Fosroc additionally offers a comprehensive package of products specifically designed for the repair and refurbishment of damaged concrete. Fosroc's 'Systematic Approach' to concrete repair features the following : hand-placed repair mortars

- spray grade repair mortars
- fluid micro-concretes
- chemically resistant epoxy mortars
- anti-carbonation/anti-chloride protective coatings
- chemical and abrasion resistant coatings

For further information on any of the above, please consult your local Fosroc office - as below.



## FOSROC İDEA YAPI KİMYASALLARI

Aydınevler Mah. Sanayi Cad.  
Demirtaş Plaza No:13 D:7-8  
Maltepe İstanbul / TÜRKİYE

[www.fosroc.com](http://www.fosroc.com)

*\* Fosroc International Limited şirketinin ticari markasıdır*

*† İlgili bilgi föyüne bakınız*

### Önemli Hatırlatma

Fosroc ürünleri malzeme ve üretim kusurlarına karşı garantili olup Fosroc Mal ve Hizmet Tedarik Koşullarına uygun olarak satılır. Tüm Fosroc bilgi föyleri düzenli olarak güncellenmektedir. En son versiyona sahip olmak kullanıcının sorumluluğundadır

**Telefon :**  
+90 216 463 69 63

**Faks :**  
+90 216 463 67 76

**email:**  
EnquiryTurkey@Fosroc.com