DATA SHEET

DEDU-SCHALUNGSSPANNSTELLE incl. cones (not mounted), with plug

Description

Formwork sapcer consisting of tie rod sleeve 22/26 mm cut to length and cone 22 mm with fitting length 10 mm. Cone bulk packed, not mounted. Supplied with plug. Special lengths on request.

Application

The formwork spacer is used to maintain the distance between the formwork and to pass the tie rods through. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Polyvinyl chloride (PVC)
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DEDU-SCHALUNGSSPANNSTELLE incl. cones (not mounted), with plug

Item no.	Ø Tube mm	Wall thickness mm	Pcs/ Bag	Pcs/ Pallet
DED15	22 / 26	150	100	1.800
DED18	22 / 26	180	100	1.800
DED20	22 / 26	200	100	1.800
DED23	22 / 26	230	100	1.800
DED25	22 / 26	250	100	1.800
DED30	22 / 26	300	100	1.800
DED35	22 / 26	350	100	1.800
DED40	22 / 26	400	100	1.800
DED50	22 / 26	500	100	1.800
DED65	22 / 26	650	50	1.800



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.