

**GIESSBETON RUNDE AUFLAGE** - with 1.0 mm eyelet wire, galvanised**Description**

Spacer with round support made of cast concrete. With eyelet wire for attachment to the reinforcement. Excellent for exposed concrete because of only one point of contact with the formwork.

**Application**

The spacer is attached to the reinforcement with the wires. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

**Material**

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)


**Packaging**

- Free of halogen-containing compounds, azo dyes, flame retardants



## GIESSBETON RUNDE AUFLAGE - with 1.0 mm eyelet wire, galvanised

Item no.	Concrete cover mm	Pcs/ Bag	Pcs/ Pallet
GBRA200	20	512	20.480
GBRA250	25	448	17.920
GBRA300	30	320	12.800
GBRA350	35	320	12.800
GBRA400	40	256	10.240
GBRA450	45	256	10.240
GBRA500	50	192	7.680
GBRA600	60	147	5.880




For further documents  
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

### Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 

 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at [www.nevoga.com](https://www.nevoga.com).

<https://www.nevoga.com/en/product/giessbeton-runde-auflage-with-1-0-mm-eyelet-wire>

Created: 30.10.2023

Page 2 / 2