

SCHALROHR NEVOTUBE® "QUADRAT"**Description**

FORMWORK TUBE NEVOTUBE® "QUADRAT"

Flexibility:

Any dimension from 150x150 mm to 800x800 mm available within 2 to 3 working days. Delivered to construction site in customised lengths. Lengths of up to 12.5 m have already been realised.

Quality:

Suitable for exposed concrete quality SB4. According to the DBV leaflet "Fair-faced concrete", the creation of a test area is required for SB4 or strongly recommended for SB3. Resistant to direct exposure to moisture. No horizontal joints of the inner liner up to a length of 4 m.

Economy:

One concreting date for many columns. This ensures optimum construction progress. Extremely light and easy to handle during transport and assembly. No crane required in most cases. Columns can be stripped in seconds using a knife. No risk of damage to the exposed concrete surface.

Environmentally friendly:

Cleaning and return transport of the formwork is not necessary. No formwork oil required. Problem-free disposal.

Application

When setting up, do not force the formwork tubes over reinforcement or spacers that may be bent too large. Position on the foundation side in the axis and fix with a wooden cross. With square and rectangular pipes as well as special shapes, pay attention to the alignment of the formwork pipes. On the ceiling side, adjust the formwork vertically with tension belts and on-site tension and pressure-resistant push-pull props and secure against uplift.

Please also note the technical application notes under "further documents", see QR code on page 2 of the data sheet.

The usability of the product in the respective installation situation must be checked by the user!

Material

- Expanded Polystyrene (EPS)
- Polyvinyl Chloride (PVC)
- Tetra Pak® Cardboard
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



SCHALROHR NEVOTUBE® "QUADRAT"

Item no.	Dimension mm	Ø Outside mm	Chamfer ~ mm	Concreting speed m/h	Concrete required ~ m³/m	Weight ~ kg/m
TM175175	175 x 175	240	13	6	0,03	2,60
TM2020	200 x 200	265	24	6	0,04	3,00
TM2424	240 x 240	313	32	6	0,06	4,30
TM2525	250 x 250	330	30	6	0,06	4,00
TM3030	300 x 300	400	30	5	0,09	5,70
TM3535	350 x 350	470	31	4	0,12	7,00
TM365365	365 x 365	500	21	3	0,13	7,50
TM4040	400 x 400	550	20	3	0,16	8,80
TM4545	450 x 450	600	42	3	0,20	10,30
TM5050	500 x 500	685	27	3	0,25	13,00



For further documents
scan or click here!

Attention: Chamfer not always exactly 45°.

For top fair-faced concrete quality! Further dimensions on request. When using self-compacting concrete, the concreting speeds have to be halved.

Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 

 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/schalrohr-nevotube-quadrat/>

Created: 30.10.2023

Page 2 / 2