

GIESSBETON FLACHE AUFLAGE "RUND" - light version, with shuttlecock clip**Description**

Round spacer with flat support made of cast concrete. With shuttlecock clip for easy attachment to the reinforcement. The shuttlecock clip ensures a secure hold at the crossing point of the reinforcement. Not suitable for exposed concrete because of the flat support.

Application

The spacer is attached to the reinforcement with the shuttlecock clip. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



GIESSBETON FLACHE AUFLAGE "RUND" - light version, with shuttlecock clip

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Pallet
GBFAL20F	20	4 - 14	384	15.360
GBFAL25F	25	4 - 14	384	15.360
GBFAL30F	30	4 - 14	320	12.800
GBFAL35F	35	4 - 14	256	10.240
GBFAL40F	40	4 - 14	192	7.680
GBFAL45F	45	4 - 14	147	5.880
GBFAL50F	50	4 - 14	147	5.880
GBFAL55F	55	4 - 14	196	7.840
GBFAL60F	60	4 - 14	147	5.880



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.




MADE IN EUROPE

info@nevoga.com

www.nevoga.com

Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/giessbeton-flache-auflage-rund-light-versic>

Created: 30.10.2023

Page 2 / 2