DATA SHEET

FASERBETON KNOCHEN OHNE DRAHT

Description

Extra strong single spacer made of fibre-reinforced concrete in bone shape. The spacers can be used for 2 or 3 different concrete covers, depending on the version.

Application

The spacer is positioned on the formwork, then the rebars are placed on the spacer. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

FASERBETON KNOCHEN OHNE DRAHT

Item no.	Concrete cover mm	Cutting width mm	Pcs/ Bag	Pcs/ Pallet
FBEK1520	15 / 20	24	1.000	20.000
FBEK20	20 / 25 / 30	22	1.000	30.000
FBEK2530	25 / 30	24	500	20.000
FBEK35	35 / 40 / 50	25	250	10.000
FBEK3540	35 / 40	28	250	10.000
FBEK4050	40 / 50	28	250	10.000
FBEK45	45 / 55 / 60	28	125	5.000
FBEK4555	45 / 55	28	150	6.000
FBEK5060	50 / 60	28	125	5.000
FBEK5565	55 / 65	28	125	5.000



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Version with two concrete covers:



Version with three concrete covers:



Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.