

SICHTBETONKEGEL- for cone with fitting length 50 mm**Description**

Cone in high-quality fair-faced concrete for closing clamping points. After removing the cone K22/5 or K26/5, the exposed concrete cone is glued into the conical opening. The cone is slightly shorter than the conical opening, which results in the formation of a shadow gap.

Application

After removing the cone, the cone is glued in place with the fibre concrete adhesive. The adhesive surfaces must be freed from dust and other dirt beforehand. The usability of the product in the respective installation situation must be checked by the user!

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET



SICHTBETONKEGEL- for cone with fitting length 50 mm

Item no.	Ø D1 mm	Ø D2 mm	Length mm	Pcs/ Box	Pcs/ Pallet
FBRK22/5	41,00	30,00	40	150	10.050



Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 

 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/sichtbetonkegel-for-cone-with-fitting-lengt>

Created: 30.10.2023

Page 2 / 2