DATA SHEET

FASERBETON TUNNELABSTANDHALTER 1.4 mm black wire, with groove, without geotextile

Description

Large-area tunnel spacer made of fibre concrete for fixing the tunnel sealing film. On request with glued-on geotextile to protect the tunnel film and available in the dimensions 80 x 80 mm or 80 x 100 mm.

Application

The spacer is used between the reinforcement and the tunnel wall for uphill fastening of the geomembranes. It is attached to the reinforcement with the wire. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

FASERBETON TUNNELABSTANDHALTER 1.4 mm black wire, with groove, without geotextile

Item no.	Concrete cover mm	Dimension mm	Pcs/ Bag	Pcs/ Pallet
FBTU40D2	40	100 x 100	25	1.000
FBTU50D1	50	100 x 100	25	1.000



Galvanised wire, other dimensions (e.g. 80x80 or 80x100 mm) or with glued-on geotextile to protect the tunnel foil on request.
Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

For further documents
scan or click here!

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.