DATA SHEET

DRUFILA-PLUS

Description

Spacer for light reinforcement with very good concrete flow. Very stable due to lateral support at the feet. Low contact with the formwork due to special feet.

Application

The spacer is laid diagonally to the reinforcement to ensure the required concrete cover. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

DRUFILA-PLUS

Item no.	Concrete cover mm	Width mm	Length m	m/ Bundle	m/ Pallet
DUFPL20/100	20	55	1,00	80,00	3.840,00
DUFPL25/100	25	55	1,00	80,00	3.520,00
DUFPL30/100	30	55	1,00	80,00	3.200,00
DUFPL35/100	35	55	1,00	80,00	2.880,00
DUFPL40/100	40	55	1,00	80,00	2.560,00
DUFPL50/100	50	55	1,00	80,00	1.920,00
DUFPL60/100	60	55	1,00	80,00	1.920,00



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L1/F/T/A.

Very strong due to lateral support at the feet.



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/drufila-plus/

Created: 30.10.2023