DATA SHEET

GIESSBETONKEGEL

Description

Cone made of cast concrete for closing clamping points. After removing the cone K22/5 or K26/5, the cast concrete cone is glued into the conical opening. Only limited suitable for fair-faced concrete.

Test certificates available:
- Watertightness test

Application

After removing the cone, the cone is glued in place with the fibre concrete adhesive. The adhesive surfaces must be freed from dust and other dirt beforehand. The usability of the product in the respective installation situation must be checked by the user!

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

GIESSBETONKEGEL

Item no.	Ø D1 mm	Ø D2 mm	Length mm	Pcs/ Bag	Pcs/ Pallet
GBK40/5	41,00	31,00	39	192	9.600



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/giessbetonkegel/

Created: 30.10.2023