

SCHALROHR NEVOTUBE® “WANDANSCHLUSSSÄULE“

Description

FORMWORK TUBE NEVOTUBE® “WANDANSCHLUSSSÄULE“

Flexibility:

Every producible dimension available within 2 to 3 working days. Delivered to construction site in customised lengths. Lengths of up to 12.5 m have already been realised.

Quality:

Suitable for exposed concrete quality SB4. According to the DBV leaflet "Fair-faced concrete", the creation of a test area is required for SB4 or strongly recommended for SB3. Resistant to direct exposure to moisture. No horizontal joints of the inner liner up to a length of 4 m.

Economy:

One concreting date for many columns. This ensures optimum construction progress. Extremely light and easy to handle during transport and assembly. No crane required in most cases. Columns can be stripped in seconds using a knife. No risk of damage to the exposed concrete surface.

Environmentally friendly:

Cleaning and return transport of the formwork is not necessary. No formwork oil required. Problem-free disposal.

Application

When setting up, do not force the formwork tubes over reinforcement or spacers that may be bent too large. Position on the foundation side in the axis and fix with a wooden cross. With square and rectangular pipes as well as special shapes, pay attention to the alignment of the formwork pipes. On the ceiling side, adjust the formwork vertically with tension belts and on-site tension and pressure-resistant push-pull props and secure against uplift.

Please also note the technical application notes under "further documents", see QR code on page 2 of the data sheet.

The usability of the product in the respective installation situation must be checked by the user!

Material

- Expanded Polystyrene (EPS)
- Polyvinyl Chloride (PVC)
- Tetra Pak® Cardboard
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



SCHALROHR NEVOTUBE® “WANDANSCHLUSSSÄULE”

Item no.	Dimension mm	Ø Outside mm	Concreting speed m/h	Concrete required ~ m³/m	Weight ~ kg/m
TN2020/W	200 x 200	310	6	0,04	3,60
TN2424/W	240 x 240	370	6	0,06	4,40
TN2525/W	250 x 250	380	6	0,06	4,50
TN3030/W	300 x 300	460	5	0,09	5,10
TN3535/W	350 x 350	530	4	0,12	5,90
TN4040/W	400 x 400	600	3	0,16	6,80
TN4545/W	450 x 450	670	3	0,20	7,90
TN5050/W	500 x 500	745	3	0,25	8,70
TR2025/W	200 x 250	352	6	0,05	4,40
TR2030/W	200 x 300	395	6	0,06	5,00
TR2035/W	200 x 350	435	6	0,07	5,70
TR2040/W	200 x 400	478	5	0,07	6,50
TR2050/W	200 x 500	582	4	0,10	7,60
TR2530/W	250 x 300	425	5	0,08	5,30
TR2535/W	250 x 350	463	5	0,08	6,20
TR2540/W	250 x 400	508	4	0,10	6,60
TR2550/W	250 x 500	600	3	0,13	7,70
TR3035/W	300 x 350	495	4	0,11	7,00
TR3040/W	300 x 400	534	3	0,12	7,60
TR3050/W	300 x 500	620	3	0,15	8,70
TR3540/W	350 x 400	562	3	0,14	8,20
TR3550/W	350 x 500	645	3	0,18	9,60
TR4050/W	400 x 500	673	3	0,20	10,40



For further documents
scan or click here!

Formwork tubes for corners on request.

For top fair-faced concrete quality! Further dimensions on request. When using self-compacting concrete, the concreting speeds have to be halved.

Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 

 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/schalrohr-nevotube-wandanschlusssaule/>

Created: 30.10.2023

Page 2 / 2