DATA SHEET

GIESSBETON 3-PUNKT AUFLAGE - with plastic clip

Description

Spacer with 3-point support made of cast concrete. With plastic clip for easy attachment to the reinforcement. Due to the low contact points with the formwork, very suitable for fair-faced concrete.

Application

The spacer is attached to the reinforcement with the plastic clip. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

GIESSBETON 3-PUNKT AUFLAGE - with plastic clip

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Pallet
GBVA25KK	25	4 - 14	384	15.360
GBVA30KK	30	4 - 14	320	12.800
GBVA35KK	35	4 - 14	256	10.240
GBVA40KK	40	4 - 14	192	7.680
GBVA45KK	45	4 - 14	147	5.880
GBVA50KK	50	4 - 14	147	5.880
GBVA55KK	55	4 - 14	147	5.880
GBVA60KK	60	4 - 14	144	5.760
GBVA65KK	65	4 - 14	108	4.320
GBVA70KK	70	4 - 14	72	2.880
GBVA75KK	75	4 - 14	72	2.880



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.