DATA SHEET

FASERBETONROLLE

Description

Strong roll spacer made of fibre concrete for rolling prefabricated reinforcement cages into formwork. Simplifies the placement of the formwork on the reinforcement cages.

Application

The spacer is pushed or plugged onto the reinforcement before the reinforcement cages are rolled in. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

FASERBETONROLLE

Item no.	Concrete cover mm	Cutting width mm	Ø Inside mm	Ø Outside mm	Pcs/ Bag	Pcs/ Pallet
FBRL35/25	35	25	13	83	100	3.000
FBRL45/25	45	25	13	102	50	2.000
FBRL50/30	50	30	14	114	40	1.600
FBRL55/30	55	30	14	124	30	1.200



Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

For further documents
scan or click here!

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/faserbetonrolle/

Created: 30.10.2023