DATA SHEET

KONUS

Description

Plastic cone for large-area transmission of the clamping forces and for protection of the formwork.
Fitting length 20 mm to 50 mm.

Application

The cone is inserted into the tie rod sleeve on one or both sides. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

KONUS

Item no.	For tube Ø mm	Fitting length mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
K22/2	22	20	250	1.000	25.000
K22/3	22	30	250	1.000	5.000
K22/5	22	50	250	-	8.000
K26/5	26	50	125	500	15.000



Note: Protect from direct sunlight during storage.



For further documents
scan or click here!

Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/konus/

Created: 30.10.2023