DATA SHEET

HOHLWANDDÜBEL - "K" with adhesive plate

Description

Hohlwanddübel for temporary fastening of props and corner brackets on double and solid walls in the assembly state. The Hohlwanddübel is positioned on the formwork at the factory using hot glue. Best possible hold due to roughened adhesive surface with Ø 50 mm. A small recess in the adhesive plate ensures minimum consumption of hot glue.
Alternatively, the Hohlwanddübel can be attached to steel formwork tables with an adhesive pad (double-sided adhesive on carrier foil). Positive side effect: No more hot glue runs into the screw guide!
A wood screw DIN 571, Ø 12 x 70 mm is used for attachment of the prop to the Hohlwanddübel. The adhesive plate can be easily removed through a predetermined breaking point. Supplied without screw and washer.

Application

The Hohlwanddübel is attached to the formwork table with hot glue. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants




DATA SHEET

HOHLWANDDÜBEL - "K" with adhesive plate

Item no.	Pcs/ Bag	Pcs/ Pallet
HWD12	250	12.500



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.