DATA SHEET

GIESSBETON FLACHE AUFLAGE "QUADRAT"- with shuttlecock clip

Description

Square spacer with flat support made of cast concrete. With shuttlecock clip for easy attachment to the reinforcement. The shuttlecock clip ensures a secure hold at the crossing point of the reinforcement. Not suitable for exposed concrete because of the flat support.

Application

The spacer is attached to the reinforcement with the shuttlecock clip. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

GIESSBETON FLACHE AUFLAGE "QUADRAT"- with shuttlecock clip

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Pallet
GBFAQ20F	20	4 - 14	512	20.480
GBFAQ25F	25	4 - 14	384	15.360
GBFAQ30F	30	4 - 14	320	12.800
GBFAQ35F	35	4 - 14	256	10.240
GBFAQ40F	40	4 - 14	192	7.680
GBFAQ45F	45	4 - 14	196	7.840
GBFAQ50F	50	4 - 14	147	5.880
GBFAQ55F	55	4 - 14	147	5.760
GBFAQ60F	60	4 - 14	98	3.920



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.