DATA SHEET

TUNNELABSTANDHALTER KUNSTSTOFF- Basis

Description

Large-area tunnel spacer made of plastic for fixing the tunnel sealing film. The open construction ensures an optimal concrete flow. Awarded with the Innovation Prize at the Austrian Tunnel Day 2010.

Application

The spacer is used between the reinforcement and the tunnel wall for uphill fastening of the geomembranes. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

TUNNELABSTANDHALTER KUNSTSTOFF- Basis

Item no.	Concrete cover mm	Dimension mm	For Ø iron mm	Pcs/ Bag	Pcs/ Pallet
KTUS30B	30	80 x 80	20	200	2.400



Note: Protect from direct sunlight during storage.



For further documents
scan or click here!

Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/tunnelabstandhalter-kunststoff-basis/

Created: 30.10.2023