DATA SHEET

T-PROFIL

Description

Multi-purpose plastic profile for covering joints (e.g. between formwork).

Application

To cover or bridge the joint, the T-profile is inserted into the joint. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyvinyl chloride (PVC)
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DATA SHEET

T-PROFIL

Item no.	Dimension "a" mm	Dimension "b" mm	Length m	m/ Bundle	m/ Pallet
T22	42	21	2,50	100,00	5.000,00



Tolerance range (dimensions) +/-1.5 mm
Tolerance range (length) +10 mm, -20 mm



Note: Protect from direct sunlight during storage.



Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/t-profil/

Created: 30.10.2023