DATA SHEET

FASERBETON EINZELABSTANDHALTER MIT HOHLKEHLE- 2 hooks across

Description

Extra strong single spacer made of fibre-reinforced concrete with groove and two cross hooks for a secure hold at the crossing point of the reinforcement.

Application

The spacer is attached to the vertical reinforcement with the hooks. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

FASERBETON EINZELABSTANDHALTER MIT HOHLKEHLE- 2 hooks across

Item no.	Concrete cover mm	Cutting width mm	Width groove mm	Depth groove mm	Pcs/ Bag	Pcs/ Pallet
FBE2H20/40/10Q	20	40	12	10	200	6.000
FBE2H25/40/10Q	25	40	12	10	150	6.000
FBE2H30/40/10Q	30	40	12	10	150	6.000
FBE2H35/40/10Q	35	40	12	10	150	6.000
FBE2H40/40/10Q	40	40	12	10	150	6.000
FBE2H45/40/10Q	45	40	12	10	150	6.000
FBE2H50/40/10Q	50	40	12	10	125	5.000



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.