DATA SHEET

GIESSBETON 3-PUNKT AUFLAGE - with 1.0 mm eyelet wire, galvanised

Description

Spacer with 3-point support made of cast concrete. With eyelet wire for attachment to the reinforcement. Due to the low contact points with the formwork, very suitable for exposed concrete.

Application

The spacer is attached to the reinforcement with the wires. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

GIESSBETON 3-PUNKT AUFLAGE - with 1.0 mm eyelet wire, galvanised

Item no.	Concrete cover mm	Pcs/ Bag	Pcs/ Pallet
GBVA20O	20	384	15.360
GBVA25O	25	384	15.360
GBVA30O	30	320	12.800
GBVA35O	35	256	10.240
GBVA40O	40	192	7.680
GBVA45O	45	147	5.880
GBVA50O	50	147	5.880
GBVA55O	55	147	5.880
GBVA60O	60	144	5.760
GBVA65O	65	108	4.320
GBVA70O	70	72	2.880
GBVA75O	75	72	2.880



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group
FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.