DATA SHEET

KUNSTSTOFFNAGEL

Description

Strong plastic nail for fastening insulation boards in concrete.

Application

Before concreting, the plastic nails for additional securing of the insulation boards are inserted through the board and concreted in. The anchoring depth in the concrete should be at least 50 mm. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

KUNSTSTOFFNAGEL

Item no.	Length mm	Board thickness mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
N075	75	≤ 25	1.000	3.000	60.000
N100	100	≥ 25	500	2.000	40.000
N125	125	≥ 50	500	1.500	30.000
N150	150	≥ 75	500	-	25.000
N175	175	≥ 100	250	-	22.750
N200	200	≥ 125	250	-	22.750
N250	250	≥ 175	250	-	16.000
N275	275	≥ 200	250	-	16.000



For further documents
scan or click here!

Length 75 to 125 mm:



Length 150 to 275 mm:



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/kunststoffnagel/

Created: 30.10.2023