GIESSBETON FLACHE AUFLAGE "RUND" - heavy version, with 1 mm eyelet wire, galvanised

Description

Extra strong, round spacer with flat support made of cast concrete. With eyelet wire for attachment to reinforcement. Not suitable for exposed concrete because of the flat support.

Application

The spacer is attached to the reinforcement with the wires. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

GIESSBETON FLACHE AUFLAGE "RUND" - heavy version, with 1 mm eyelet wire, galvanised

Item no.	Concrete cover mm	Pcs/ Bag	Pcs/ Pallet
GBFAS20O	20	384	15.360
GBFAS25O	25	320	12.800
GBFAS30O	30	256	10.240
GBFAS35O	35	192	7.680
GBFAS40O	40	196	7.840
GBFAS45O	45	147	5.880
GBFAS50O	50	147	5.880
GBFAS60O	60	98	3.920



For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.