

ABSTANDHALTER HORIZONTAL**Description**

Strong plastic spacer with elastic clamping unit.

Application

The spacer is attached to the reinforcement with the clamp. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants




ABSTANDHALTER HORIZONTAL


Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet
H10	10	4 - 16	1.000	8.000	40.000
H15	15	4 - 16	1.000	6.000	36.000
H20	20	4 - 16	500	4.000	32.000
H25	25	4 - 16	500	3.500	28.000
H30	30	4 - 16	250	2.500	25.000
H35	35	4 - 16	250	1.500	24.000
H40	40	4 - 16	250	1.250	25.000
H45	45	4 - 16	125	1.000	12.000
H50	50	4 - 16	125	1.000	12.000



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE ZNOJMO | CZ BIESIEKIERZ | PL 
 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/abstandhalter-horizontal/>

Created: 30.10.2023

Page 2 / 2