# DATA SHEET

## KUPPLUNG - for water barrier

**Description**

Coupling for water stop to reduce the diameter of the water stop to match the diameter of 22 mm of tie rod sleeves.

**Application**

The coupling is fitted onto the water stop and then inserted into a tie rod sleeve with an inner diameter of 22 mm. The usability of the product in the respective installation situation must be checked by the user!

**Material**

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

**Packaging**

- Free of halogen-containing compounds, azo dyes, flame retardants

# DATA SHEET

## KUPPLUNG - for water barrier

| Item no. | Length mm | Pcs/ Bag | Pcs/ Big bag | Pcs/ Pallet |
|---|---|---|---|---|
| DIKUW22N | 40 | 250 | 2.500 | 30.000 |



Note: Protect from direct sunlight during storage.



**Nevoga Group**

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

**https://www.nevoga.com/en/product/kupplung-for-water-barrier/**

Created: 30.10.2023