

FASERBETON KNOCHEN MIT DRAHT**Description**

Extra strong single spacer made of fibre-reinforced concrete in bone shape with wire for attachment to the reinforcement. The spacers can be used for 2 or 3 different concrete covers, depending on the version.

Application

The spacer is attached to the reinforcement with the wires. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



FASERBETON KNOCHEN MIT DRAHT

Item no.	Concrete cover mm	Cutting width mm	Pcs/ Bag	Pcs/ Pallet
FBEKD1520	15 / 20	24	1.000	20.000
FBEKD20	20 / 25 / 30	22	500	25.000
FBEKD2530	25 / 30	24	500	20.000
FBEKD35	35 / 40 / 50	25	250	10.000
FBEKD3540	35 / 40	28	250	10.000
FBEKD4050	40 / 50	28	250	10.000
FBEKD45	45 / 55 / 60	28	125	5.000
FBEKD4555	45 / 55	28	150	6.000
FBEKD5060	50 / 60	28	125	5.000
FBEKD5565	55 / 65	28	125	4.000



For further documents
scan or click here!

Galvanised wire on request.

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Version with two concrete covers:



Version with three concrete covers:



Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 

 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/faserbeton-knochen-mit-draht/>

Created: 30.10.2023

Page 2 / 2