DATA SHEET

RINGABSTANDHALTER "PILING"- closed

Description

Spacers specially developed for the use of pile cages. Also suitable for diaphragm walls.

Application

The spacer is placed on the reinforcement before the reinforcement cage is inserted into the pile hole. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

RINGABSTANDHALTER "PILING"- closed

Item no.	Concrete cover mm	For Ø iron mm	Pcs/ Roll	Pcs/ Pallet
R50GBGN	50	6 - 20	45	4.500
R75GBGN	75	6 - 20	45	2.205



Note: Protect from direct sunlight during storage.



For further documents
scan or click here!

Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/ringabstandhalter-piling-closed/

Created: 30.10.2023