

GIESSBETON FLACHE AUFLAGE "RUND" - light version, with 1 mm eyelet wire, galvanised**Description**

Round spacer with flat support made of cast concrete. With eyelet wire for attachment to reinforcement.
Not suitable for exposed concrete because of the flat support.

Application

The spacer is attached to the reinforcement with the wires. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Cast concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



GIESSBETON FLACHE AUFLAGE "RUND" - light version, with 1 mm eyelet wire, galvanised

Item no.	Concrete cover mm	Pcs/ Bag	Pcs/ Pallet
GBFAL200	20	384	15.360
GBFAL250	25	384	15.360
GBFAL300	30	320	12.800
GBFAL350	35	256	10.240
GBFAL400	40	192	7.680
GBFAL450	45	147	5.880
GBFAL500	50	147	5.880
GBFAL550	55	196	7.840
GBFAL600	60	147	5.880




For further documents
scan or click here!

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/T/A.

Nevoga Group

FREILASSING | DE 

ZNOJMO | CZ 

BIESIEKIERZ | PL 

 MADE IN EUROPE

info@nevoga.com

www.nevoga.com



All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

<https://www.nevoga.com/en/product/giessbeton-flache-auflage-rund-light-versic>

Created: 30.10.2023

Page 2 / 2