DATA SHEET

HOHLWANDDÜBEL - "M" for magnet

Description

Hohlwanddübel for temporary fastening of props and corner brackets to double and solid walls in the assembly state.
The Hohlwanddübel is positioned on the steel formwork with the reusable magnet. After stripping the formwork, the magnet usually remains on the formwork due to its high adhesive force.
A wood screw DIN 571, Ø 12 x 80 mm is used for attachment of the prop to the Hohlwanddübel. Supplied without magnet, screw and washer.

Application

The Hohlwanddübel is attached to the formwork table with the appropriate magnet. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

HOHLWANDDÜBEL - "M" for magnet

Item no.	Pcs/ Bag	Pcs/ Pallet
HWDM12	250	12.500





Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/hohlwanddubel-m-for-magnet/

Created: 30.10.2023