DATA SHEET

FASERBETON STOPFEN

Description

Fibre-reinforced concrete plug for closing the fibre-reinforced concrete tube with diameter 22 mm.

Test certificates available:
- Watertightness test
- Fire behaviour F180
- Airborne sound insulation
- Drinking water suitability

Application

After removing the formwork, the tie rod and the cone, the plug is glued into the fibre-reinforced concrete tube with the fibre-concrete adhesive. The fibre-reinforced concrete tube must be cleaned of dust and other dirt beforehand. The usability of the product in the respective installation situation must be checked by the user!

Material

- Fibre-reinforced concrete
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

FASERBETON STOPFEN

Item no.	For tube Ø mm	Length mm	Pcs/ Bag	Pcs/ Pallet
FBRST22/20	22	20	1.000	40.000
FBRST22/50	22	50	500	20.000



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/faserbeton-stopfen/

Created: 30.10.2023