

DRUNTERLEISTE VOLL- strong, closed at the side**Description**

Linear, labour-saving plastic spacers for lower reinforcement for all applications where the reinforcement has to be set against soft surfaces, e.g. insulation boards. For this purpose, the Drunterleiste is placed with the flat side on the insulation.

Application

The spacer is laid diagonally to the reinforcement to ensure the required concrete cover. The usability of the product in the respective installation situation must be checked by the user! Further information on the arrangement and installation distances can be found in the relevant DBV leaflets.

Material

- Polyvinyl chloride (PVC)
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants



DRUNTERLEISTE VOLL- strong, closed at the side

Item no.	Concrete cover mm	Length m	m/ Bundle	m/ Pallet
DLZV15/200	15	2,00	100,00	7.700,00
DLZV20/200	20	2,00	100,00	6.300,00
DLZV25/200	25	2,00	100,00	5.600,00
DLZV30/200	30	2,00	100,00	4.200,00
DLZV35/200	35	2,00	60,00	3.960,00
DLZV40/200	40	2,00	60,00	2.400,00
DLZV45/200	45	2,00	60,00	1.920,00
DLZV50/200	50	2,00	60,00	1.680,00
DLZV55/200	55	2,00	40,00	1.760,00
DLZV60/200	60	2,00	40,00	1.200,00
DLZV70/200	70	2,00	40,00	1.120,00
DLZV75/200	75	2,00	40,00	1.120,00
DLZV80/200	80	2,00	20,00	1.040,00



For further documents
scan or click here!

Further lengths on request.

Tested according to DBV leaflet „Abstandhalter“ DBV - c - L2/F/A.

Note: Protect from direct sunlight during storage.

