DATA SHEET

ROHRKLIPP

Description

Pipe clip for heating and cooling coils of concrete core activation for clean, simple and most importantly efficient positioning of the pipelines for concrete core temperature control. The pipe clip can be positioned in the fresh concrete or in the insulation. Suitable for pipe diameters up to max. 20 mm.

Application

The Rohrklipp is pressed with its tips into the fresh concrete or insulation. Pipes up to a diameter of max. 20 mm can then be laid. The usability of the product in the respective installation situation must be checked by the user!

Material

- Polyolefin PO (High-density polyethylene HD-PE + Polypropylene PP)
- Free from PVC, CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

ROHRKLIPP

Item no.	Mounting height mm	Base plate mm	Peak length mm	Pcs/ Box	Pcs/ Pallet
RK	68	34 x 79	40	250	6.000



Alternative application with reinforcing bars:



For further documents
scan or click here!

Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE
ZNOJMO | CZ
BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/rohrklipp/

Created: 30.10.2023