DATA SHEET

DICHTSTOPFEN

Description

Flexible plug for optimal sealing of tie rod sleeves and formwork spacers.

Application

The sealing plug is inserted into the tie holes after removing the formwork. For easier insertion of the sealing plugs, we recommend the grip mandrel (item no.: GRD). The usability of the product in the respective installation situation must be checked by the user!

Material

- Soft PVC (PVC-P)
- Free from CFC and HFC
- Without substances of very high concern according to ECHA candidate list (REACH Regulation)

Packaging

- Free of halogen-containing compounds, azo dyes, flame retardants

DATA SHEET

DICHTSTOPFEN

Item no.	For tube Ø mm	Pcs/ Bag	Pcs/ Big bag	Pcs/ Pallet	Fitting length mm
DS20	20	500	2.500	25.000	-
DS22	22	500	2.500	50.000	-
DS26	26	500	-	20.000	-



Note: Protect from direct sunlight during storage.



Nevoga Group

FREILASSING | DE

ZNOJMO | CZ

BIESIEKIERZ | PL

MADE IN EUROPE info@nevoga.com www.nevoga.com

All information has been prepared to the best of our knowledge and according to the current state of the art. However, Nevoga does not guarantee the accuracy and completeness of the information. This data sheet is updated on an ongoing basis. Nevoga therefore reserves the right to make changes without prior notice to the customer. The latest version can be found at www.nevoga.com.

https://www.nevoga.com/en/product/dichtstopfen/

Created: 30.10.2023